

HIGH ENERGY VORTEX
WATER TREATING
SYSTEMS

Hammonds

HTS-80P
Manual Chlorinator

Vortex Tablet Chlorination

SYSTEMS



FLUID TECHNOLOGY



The Hammonds advanced technology vortex chlorinator takes the mystery out of on-site, engineered tablet chlorination. Not to be confused with adapted swimming pool feeders, Hammonds chlorinators are designed from scratch for municipal and industrial disinfection. A high energy vortex mixing chamber with no moving parts produces calcium hypochlorite solution at less than 1/4% (0.25%) concentration precisely metered by a positive displacement pump providing disinfection for wells to 2000 GPM. Single phase 110 VAC power at 5 amps and a water source of 8 GPM is all that is required to provide consistent stable residuals in potable and wastewater treatment. Hammonds vortex tablet chlorination systems, are the state-of-the-art in water treatment systems.

Contact a Hammonds water treatment specialist today.

U.S. Patents: 6,337,024 B1 • 6,451,271 B1 • 6,531,056 B2

ADD THIS TO
NEW DESCRIPTION

SPECIFICATIONS

- Tablet recommendations: NSF® std. 60 listed solid calcium hypochlorite only.
- Performance: Typical 50-2000 GPM wells at dosing levels up to 2 PPM
- Chlorine delivery: 0-3.0 pounds per hour. Delivery will vary depending on size and manufacture of calcium hypochlorite tablet
- Solution metering pump:
 - Type: Balanced diaphragm, positive displacement
 - Performance: 0-3 GPM
- Chlorine delivery controls:
 - Manual: Pump speed with variable control
 - Automatic flow pacing: Automatically adjusts pump speed when supplied with 4-20mA signal from process flow meter
- Tablet capacity: 80 lbs.
- Water required: 8 GPM clear, potable at pressures of 30-150 PSI
- Power: 110 VAC @ 3 amps
- Discharge pressure: Up to 150 PSI, higher pressures available
- Inlet pressure: 30 - 150 PSI
- Frame material: Hot dip galvanized angle iron
- Leveling legs: (4) stainless steel adjustable with leveling bubble
- Dimensions: 24" W x 60" H x 49" L
- Weight: 260 lbs.

CONSTRUCTION MATERIALS

- Frame: 1/2" x 1/2" hot dip galvanized steel
- Mixing reservoir: 30 gallon - polyethylene (actual used capacity approximately 6 gallons)
- Tablet feeder: PVC
- Solution tank: 25 gallon polyethylene 12" W x 20 1/2" H x 20" L)
- Piping: Sch. 80 PVC
 - Inlet water supply at bulkhead: 1" Sch. 80 PVC
 - Outlet 1/2" fnpt
 - Circulation to mixing reservoir: 3/4" Sch. 80 PVC
 - Discharge from circulation reservoir to solution tank: 2" Sch. 80 PVC
 - Suction feed to pump: 1" nylon re-enforced PVC clear hose, PVC hose barbs
 - Pump discharge manifold to system outlet: 3/8" nylon re-enforced PVC tubing with PVC hose barbs
- Relief valve: Sch. 80 PVC
- Flow limiting valve: PVC
- Unions/bulkhead fittings: Sch. 80 PVC
- Pump suction strainer: PVC
- Pump:
 - Fluid end: Polypropylene
 - Elastomers: Viton®
 - Lube oil: Food grade
 - Valves: 316 S.S.
 - Diaphragm: Viton®

ELECTRICAL SPECIFICATIONS

Enclosure: UL® listed NEMA 4X
Power supply: 110 VAC @ 5 amps, actual consumption less than 5 amps
Pump motor: 1/3 hp, variable speed, TEFC, 90 VDC

OPTIONAL EQUIPMENT: Chlorine analyzer, chart recorder, back-up injection pump, remote panel for controls, analyzer, and recorder

CERTIFICATIONS

INNOVATION—pure and simple

To contact a Hammonds water treatment specialist, please call (800) 582-4224.

Hammonds

HAMMONDS WATER TREATMENT SYSTEMS

910 Rankin Road • Houston, Texas 77073
Phone (800) 582-4224 • Fax (281) 847-1857
www.waterchlorination.com



SPECIFICATIONS

- Tablet recommendations: NSF®Std. 60 listed solid calcium hypochlorite only
- Performance: Typical 50 – 2,000 GPM wells and fresh water supply at dosing levels up to 2 PPM
- Chlorine delivery: 0 – 3.0 pounds of chlorine per hour. Delivery will vary depending on size and manufacture of calcium hypochlorite tablet.
- Solution metering pump:
 - Type: Diaphragm, positive displacement, variable stroke and variable speed
 - Performance: 0 – 2.75 GPM
- Chlorine delivery controls:
 - Manuel: Pump speed with variable control, panel mounted
 - Automatic flow pacing: Automatically adjusts pump speed when supplied with 4-20mA signal from process flow meter or chlorine analyzer
 - Solution Strength: Solution concentration can be varied by adjustment of Vortex by-pass water. (8 GPM feed water remains unchanged)
- Tablet Capacity: 80 lbs.
- Water required: 8 GPM clear, potable at pressures of 30 – 75 PSI (Feed water pressures above 75 PSI requires an optional inlet pressure regulator)
- Frame: Laser cut, hot dip galvanized steel
- Leveling legs: (4) stainless steel adjustable with leveling bubble
- Dimensions:
- Weight:

ELECTRICAL SPECIFICATIONS

- Enclosure: UL®listed NEMA 4X
- Power supply: 110 VAC @ 5 amps
- Pump Motor: 1/3 hp, variable speed TEFC, 90 VDC
- SCADA READY

MATERIALS OF CONSTRUCTION

- Frame: Laser cut, hot dip galvanized steel with hot dip galvanized fasteners
- Tablet feeder (eroder): PVC
- Mixing chamber: HDPE tank with all PVC internal components including lid
- Solution tank: 33 gallon, HDPE 24”L x 18”Wx 18”H
- Piping: Sch. 80 PVC
 - Inlet water supply at bulkhead: 1” Sch. 80 PVC
 - System Outlet: ½” FNPT
 - All piping is Sch. 80 PVC or 1” nylon reinforced PVC clear tubing
- Relief valve: Sch. 80 PVC
- Flow limiting valve: PVC

- All pipe and hose fittings: Sch. 80 PVC
- Bulkhead Fittings: HDPE spin welded and Sch. 80 PVC
- Pump Suction Strainer: PVC
- Pump:
 - Fluid end: PVC,
 - Valves: Ceramic with Viton® trim
 - Diaphragms: Teflon®/EPDM

OPTIONAL EQUIPMENT




- Chlorine analyzer, chart recorder, back-up injection pump, inlet pressure regulator, inlet strainer

CERTIFICATIONS

- Entire system is NSF® 61 listed (pending), Hammonds is ISO 9001:2015 , Hammonds is a UL® certified mfg. facility™


SYSTEM TECHNOLOGY

The latest generation HTS-80-P2 Vortex tablet chlorinator marks 25 years of proven performance and dependability in water disinfection. Improvements in eroder design significantly reduces maintenance labor and personnel contact with chemicals. TKM™ heavy duty diaphragm pumps with adjustable stroke in addition to Hammonds variable speed controls provide precise, repeatable metering of calcium hypochlorite solution for a variety of disinfection applications. The standard HTS-80-P2 is SCADA ready and can be controlled manually or paced automatically by a 4-20 mA signal from a chlorine analyzer or process flow meter. Hammonds' patented Vortex tablet eroder operates on a fixed 8 GPM water supply that produces an adjustable strength calcium hypochlorite solution from 0 – 0.25% concentration. The HTS-80-P2 is a complete system out of the box powered by a 20 amp 110 VAC circuit providing consistent residuals for potable and waste water treatment.



WE CAN REDUCE THE SIZE OF THESE DIMENSIONS - THERE MAY BE ROOM TO ADD THE TOP VIEW

No
The information and spe
PRO
AND IS THE EX
HAMMONDS TEC
AND MAY NOT BE USED, CO
OR PART WITHOUT THE
Hammonds Tech



WE WILL CHANGE THIS ILLUSTRATION WITH A NEW DWG.

